

CUE ONE



CUE ONE

3-way high output ultra low profile stage monitor

- 3-way coherent point source technology
 - Double 12" and 1.4" coax driver
 - Asymmetrical vertical coverage 55° + 40°
 - Outstanding audio quality
 - Ultra low feedback
 - Ultra low profile design
- Integrated hardware for increased dispersion
 - Powerful low frequency response
 - Mechanically durable
 - Discrete cables connection
 - Passive or bi-amp operation
 - Light weight

- System components: RC20 Rack, DNC260, C10, SC4

The cabinet contains double 12" extremely high power neodymium woofers and a 1.4" coaxial compression driver loaded by an asymmetrical 60° x 55°+40° elliptical wave-guide.

The CUE ONE has the power handling and power output to suite the largest of monitoring applications, while still being discreet and low profile in physical form. Unique cabling format and integrated hardware for adjusting dispersion along with a rotatable HF wave guide provide users total flexibility of use. The CUE ONE's design and the technologies used, truly allow monitor engineers to be creative with their on stage audio designs, bring that same level of Audio attention to be found at the FOH to the stage.

ACCESSORIES

- | | |
|----------|------------------------------------|
| A1HC | Horizontal U-bracket for CUE ONE |
| A1WM | Wall mount bracket for CUE ONE |
| FC1CUE | Flight case for 2x CUE ONE |
| CFA | Flying Adapter for CUE-Series |
| CSF | Stand fitting for CUE-Series |
| CO SC8x2 | Protection cover for 2x SC8 / SC8F |

TECHNICAL SPECIFICATIONS CUE ONE	
Type:	3-way high output stage monitor
Application:	Stage monitor
Frequency response:	54 Hz - 21 kHz (-3 dB)
Power handling AES:	2000 W
Peak Power:	8000 W
Sensitivity:*	104 dB
Max. SPL peak:	143 dB
Dispersion:	
Horizontal:	60°
Vertical:	55° + 40°
Components:	
Low frequency:	2 x 12" neodymium woofer, 4" (101.6 mm) voice coil, 1000 W
High frequency:	1.4" neodymium coaxial driver 3.5" (90 mm), + 1.75" (44.4 mm) voice coil, 150 W + 80 W
Crossover:	750 Hz passive or bi-amp (internal connector), 6.3 kHz passive
Nominal impedance:	4 Ohm
Input connectors:	2x Neutrik™ NL4MP
Enclosure material:	15 / 18 mm plywood
Finish:	Textured black paint
Dimensions:	670 x 322 x 627 mm
Net weight:	32 kg

* Half-space loading