## G308



- Extreme compact multidesign enclosure
- Wide coverage angles
- 1" patented compression driver

- Multiple fly-points for easy hanging
- Extended accessories range for both touring and installation
- System components: DNC260, C-Series Amplifiers, G15-SUB, G18-SUB

TECHNICAL SPECIFICATIONS G308	
Туре:	2-way full range system, multidesign enclosure
Application:	High quality short throw
Frequency response:	70 Hz - 30 kHz (-3 dB)
Power handling AES:	220 W
Program power:	440 W
Peak power:	880 W
	94.5 dB
	124 dB
	90° conical
	8" ultra low distortion cone driver, 2" voice coil
	1" compression driver, 1.5" voice coil
Crossover point:	1900 Hz
Nominal impedance:	8 Ohm
Input connectors:	2x Neutrik™ NL4MP
Enclosure material:	Birch plywood
Suspension:	2x M6 threaded points
Dimensions (WxHxD):	230 x 471 x 260 mm
Net weight:	9.5 kg
	Human EQ-switch

The Coda Audio G308 is a compact versatile full range 2-way loudspeaker system that features an 8" ultra low distortion low frequency driver and a 1" compression driver coupled to a 90° conical wood waveguide.

The G308 incorporates a multidesign enclosure fitted with M6 flying points enabling it to be used horizontal, vertical or as a floor monitor.

## ACCESSORIES

FC308	Flight case for 2 x G308
A8VG	Vertical U-bracket for G308
A8HG	Horizontal U-bracket for G308
GFA	Flying Adapter for G308
GSF	Stand fitting for G308
M6 Ring	for rigging G308
A68620	Truss Clamp for G308